

IAP17 Rec'd PCT/PTO 28 APR 2006

APPARATUS AND METHOD FOR RECEIVING DATA BROADCASTING
SERVICE TO SUPPORT CONNECTION WITH MOBILE NETWORKSDisclosure5 Technical Field

The present invention relates to a data broadcasting receiving apparatus supporting a function of accessing to a mobile communication network and a method thereof; and, more particularly, to an apparatus for downloading upgrade software by being connected to a mobile communication network in digital broadcasting mobile and fixed reception environments and providing an interactive service by using the upgrade software, and a method thereof.

15

Background Art

In the age of digital broadcasting, diverse specifications are used according to regions and media such as terrestrial waves, satellite and cable. Digital broadcasting receivers and mobile terminals connected to a mobile communication network, too, have interface with an external device based on diverse access specifications according to regions and providers.

25 The interface specification is expected to be developed further, as it accommodates new technology to satisfy the convenience and demand of the service providers.

For example, the portable digital terminals provided by each mobile communication terminal manufacturers and laptop computers have different interface specifications. In order to connect the terminals or the laptop computers with an external device, different matching specifications and connection protocols should be used.

35 However, it takes long time for a digital broadcasting

receiving apparatus to be widespread. Therefore, if a user should purchase digital broadcasting receiving apparatus whenever a new matching specification with the mobile communication terminal is introduced, it will bring
5 economical burden to users as well as delaying the service introduction time and thus dropping business feasibility.

To overcome the problem, required is a digital broadcasting receiving apparatus that can be upgraded by downloading software to be added to provide a new service
10 through a broadcasting network or a communication network.

The data broadcasting receiving apparatus having a software downloadable structure is favorable for the introduction of a new service. Also, it can be applied to diverse media and regions with the same platform.

15 Therefore, the users do not need to purchase the broadcasting receiver according to the communication service providers and the kind of the mobile communication terminal and thus they can save the burden of additional purchase. The service providers also can improve the
20 business performance by providing a new service based on the large-volume data broadcasting equipment.

Therefore, a new receiving apparatus and method that can upgrade the access function of diverse mobile communication terminals by upgrading the access and
25 protocols through the broadcasting network and the communication network are required necessarily.

Disclosure

Technical Problem

30

It is, therefore, an object of the present invention to provide a data broadcasting receiving apparatus that can be connected with mobile communication terminals of diverse connection specifications by upgrading middleware or a
35 plug-in software conveniently in a digital broadcasting

mobile and fixed reception, and a method thereof..

The other objects and advantages of the present invention can be easily understood by those skilled in the art.

5

Technical Solution

In accordance with one aspect of the present invention, there is provided a data broadcast receiving
10 apparatus capable of supporting an interactive service, which includes: a demultiplexer for separating signals transmitted from the outside into signals of a kind; a controller for controlling elements of the data broadcast receiving apparatus, receiving and outputting contents
15 separated in the demultiplexer; a download processor for receiving downloadable data divided in the demultiplexer, determining the kind of the downloadable data, and performing upgrade by downloading the downloadable data; and a mobile terminal accessing unit for accessing to a
20 mobile communication network based on the downloadable data.

In accordance with one aspect of the present invention, there is provided a data broadcast receiving apparatus supporting an interactive service, which
25 includes: a demultiplexer for dividing signals from the outside into signals of a kind; a controller for controlling elements of the data broadcast receiving apparatus, receiving and outputting contents divided in the demultiplexer; a download processor for receiving
30 downloadable data divided in the demultiplexer, determining the kind of the downloadable data, and performing upgrade by downloading the downloadable data; and a mobile terminal accessing unit for accessing to a mobile communication network based on the downloadable data.

35 In accordance with one aspect of the present

invention, there is provided a method for upgrading software by using downloaded data inputted from the outside in a data broadcast receiving apparatus, which includes the steps of: a) selecting downloadable data from broadcast
5 stream in the data broadcast receiving apparatus; b) determining the kind of the downloadable data; and c) upgrading the software according to the kind of the downloadable data.

In addition, the method for upgrading the software in
10 the data broadcasting receiving apparatus based on the data downloaded from the outside further includes a step of connecting the mobile terminal, in which the mobile communication network connection request is received from the user and processed.

15

Advantageous Effect

A data broadcasting receiving apparatus of the present invention can upgrade middleware or plug-in software easily
20 in digital broadcasting mobile and fixed reception environments and thereby it can be easily connected with a mobile communication terminal that is changed continuously.

Also, the present invention provides the following economical advantages on the parts of users, broadcasting
25 stations, and receiving apparatus manufacturers.

First, the users can save the cost for purchasing and maintaining equipment by removing an additional cost for frequent upgrade of the receiving apparatus in the long run.

30 Secondly, the broadcasting station can increase the broadcasting quality through application upgrades, as the receiving apparatus supports software upgrade and provides diverse data broadcasting services. Thus, the broadcasting station can shorten the time for propagating the receiving
35 apparatus that supports the software upgrade.

Thirdly, since the software upgrade for the receiving apparatus is supported on the network, the receiving apparatus manufacturers can save the human and material resources needed for maintaining and repairing the receiving apparatuses.

Brief Description of Drawings

The above and other objects and features of the present invention will become apparent from the following description of the preferred embodiments given in conjunction with the accompanying drawings, in which:

Fig. 1 is a block diagram illustrating a data broadcasting receiving apparatus supporting an access to a mobile communication network in accordance with an embodiment of the present invention; and

Fig. 2 is a block diagram illustrating a processor and an interaction between the processor and a mobile terminal accessing unit 29 in accordance with an embodiment of the present invention.

Best Mode for the Invention

Other objects and aspects of the invention will become apparent from the following description of the embodiments with reference to the accompanying drawings, which is set forth hereinafter.

The following description provides an example of the principle of the present invention. Thus, those skilled in the art can realize the principle of the present invention and invent diverse apparatuses in the concept and scope of the present invention, although they are not described definitely or illustrated. Also, the conditional terms and embodiments presented in the present patent specification are definitely intended only for the purpose of

understanding and the present invention is understood not limited to the embodiments and the conditions described in the specification.

In addition, all detailed descriptions of a particular
5 embodiment as well as the principle, viewpoints and
embodiments of the invention should be understood to
include their structural and functional equivalents. The
equivalents are understood to include not only currently
known equivalents and equivalents to be invented in future,
10 that is, all devices invented to perform the same
functions, regardless of the structures.

Therefore, the block diagrams of the present invention
should be understood to present a conceptual viewpoint of
an exemplary circuit materializing the principle of the
15 present invention. Similarly, flowcharts, state diagrams,
and pseudo codes can be substantially expressed in a
computer-readable recording medium, and they should be
understood to show diverse processes performed by a
computer or a processor, whether or not a computer or a
20 processor is illustrated clearly.

The functions of diverse devices illustrated to
include a processor or a functional block similar to a
processor can be provided as dedicated hardware or hardware
capable of executing proper software. When the functions
25 are provided by a processor, the functions can be provided
by a single dedicated processor, a single shared processor
or a plurality of individual processors and part of them
can be shared..

The clear use of a term presented as a processor,
30 control, or a similar concept should not be construed to
refer to exclusively hardware capable of performing
software and it should be understood to implicatively
include a digital signal processor (DSP) hardware and Read
Only Memory (ROM), Random Access Memory (RAM) and non-
35 volatile memory for storing software without any

limitation. Other known and widely used hardware can be included.

In the claims of the present specification, an element expressed as a means for performing a function described in
5 the detailed description is intended to include all methods for performing the function including all formats of software, such as combinations of circuits for performing the intended function, firmware/microcode and the like.

To perform the intended function, the element is
10 cooperated with a proper circuit for performing the software. The present invention defined by claims includes diverse means for performing particular functions, and the means are connected with each other in a method requested in the claims. Therefore, any means that can provide the
15 function should be understood to be an equivalent to what is figured out from the present specification.

Other objects and aspects of the invention will become apparent from the following description of the embodiments with reference to the accompanying drawings, which is set
20 forth hereinafter. The same reference numeral is given to the same element, although the element appears in different drawings. In addition, if further detailed description on the related prior arts is determined to blur the point of the present invention, the description is omitted.
25 Hereafter, preferred embodiments of the present invention will be described in detail with reference to the drawings.

Fig. 1 is a block diagram illustrating a data broadcasting receiving apparatus supporting an access to a mobile communication network in accordance with an
30 embodiment of the present invention.

As illustrated in Fig. 1, the data broadcasting receiving apparatus of the present invention includes: a processor 10, a radio frequency (RF) tuner/demultiplexer 21, a Moving Picture Experts Group (MPEG)-2 AV decoder 22,
35 a memory 23, a graphic processor 24, a video output unit

25, an audio output unit 26, a peripheral processor 27, a software download processor 28, and a mobile terminal accessing unit 29.

The elements of the data broadcasting receiving apparatus suggested in the present invention are operated as follows.

The RF tuner/demultiplexer 21 receives terrestrial RF signals and classifies the signals into audio, video, contents and download data through modulation and demodulation according to the kind of a signal based on each bit stream.

The processor 10 controls the elements of the data broadcasting receiving apparatus, receives and processes contents classified in the RF tuner/demodulator 21, and outputs them through the graphic processor 24, the audio output unit 26, and the video output unit 25.

The software download processor 28 receives the downloaded data, determines a software module to be upgraded to be connected with the mobile communication terminal, and performs software upgrade.

Herein, the 'upgrade' signifies a process of setting up new software, such as plug-in program, as well as all the processes of setting up software whose version is different from that of the pre-established software.

The MPEG-2 AV decoder 22 receives audio and video classified in the RF tuner/demodulator 21, decodes them based on the MPEG-2 specification, and outputs them through the video output unit 25 and the audio output unit 26, individually.

The mobile terminal accessing unit 29 is cooperated with the software upgraded in the software download processor 28 and accesses to the mobile communication network through the mobile communication terminal.

Fig. 2 is a block diagram illustrating a processor and an interaction between the processor and a mobile terminal

accessing unit 29 in accordance with an embodiment of the present invention.

As shown in Fig. 2, the processor 10 of the present invention includes middleware 11 and an operating system 12
5 and connected with the software download processor 28 and the mobile terminal accessing unit 29.

Herein, the middleware 11 outputs a control signal 13 to the software download processor 28 and it is provided with plug-in software and a middleware module for upgrade,
10 which is stored in the memory 23 for the connection with the mobile communication terminal, from the software download processor 28. The software for connection with the mobile communication terminal can be the middleware module or the plug-in software.

15 Also, the operating system 12 performs a connection process by exchanging control signals 14 and 15 for connection to the mobile communication network with the middleware 11 and the mobile terminal accessing unit 29, and it transmits/receives interactive data.

20 The middleware 11 and the operating system 12 of the processor 10, the software download processor 28, and the mobile terminal accessing unit 29 are operated as follows.

When the middleware module is upgraded, the software download processor 28 checks out whether the middleware 11
25 is in operation based on the control signal 13.

If the middleware 11 is in operation, the resources of the software download processor 28 are suspended, and the operating system resources assigned for the operation of the middleware are suspended by outputting the control
30 signal 14 to the operation system 12 through the middleware 11.

The operating system 12 informs the middleware 11 of the suspension of the operating system resources through the control signal 14 so that the middleware 11 comes to a
35 complete suspension. Subsequently, the middleware 11

informs the software download processor 28 of the suspension through the control signal 13, and the software download processor 28 performs upgrade in the middleware 11 by transmitting the middleware module to the middleware 11.

5 After the upgrade of the middleware module is completed, the middleware 11 transmits a signal for resuming the operation of the middleware to the software download processor 28 based on the control signal 13 transmitted from the software download processor 28.

10 Also, in case where the plug-in software is set up for middleware plug-in, the software download processor 28 transmits the middleware plug-in to the middleware 11 regardless of the state of the middleware 11 and sets up the plug-in software in the middleware 11.

15 Subsequently, the software upgraded to be connected to a mobile communication terminal performs the connection process by exchanging the control signal 15 for connection with the mobile communication network with the mobile terminal accessing unit 29 under the control of the
20 operating system 12.

 Figs. 3 and 4 are flowcharts describing the software downloading process and the mobile communication network accessing process in accordance with an embodiment of the present invention. The flowcharts describe the operation of
25 the software download processor 28 and the mobile terminal accessing unit 29 in accordance with an embodiment of the present invention. The software download processor 28 downloads and sets up the upgrade software which is transmitted through the broadcasting network, and the
30 mobile terminal accessing unit 29 accesses to the mobile communication network by using the upgrade software.

 First, at step S30, the software download processor 28 monitors broadcast stream transmitted to the RF tuner/demultiplexer continuously and, at step S31, it
35 determines whether there is a downloadable data information

descriptor.

Herein, the downloadable data information descriptor includes Program Specific Information (PSI) of the MPEG-2 system, Data Service Table (DST) of the Advanced Television
5 Systems Committee (ATSC) data broadcasting, Application Information Table (AIT) of the DVB-Multimedia Home Platform (MHP), and System Information (SI) of the Digital Multimedia Broadcasting (DMB).

If it is determined that there is no downloadable data
10 information descriptor at the step S31, the logic flow goes to the step S30 to continue to monitor the broadcast stream. If there is a downloadable data information descriptor, at step S33, the contents of the downloadable data information is examined.

15 Subsequently, at step S35, it is determined whether the examined downloadable data information descriptor includes downloadable data identification, which is information for identifying the data format of the downloadable data.

20 If there is no downloadable data identification at the step S35, the logic flow goes to the step S30 to monitor the broadcast stream. Otherwise, if there is downloadable data identification, at step S37, the downloadable data identification is stored in the memory 23.

25 Subsequently, at step S39, the kind of the downloadable data is determined based on the above-stored downloadable data identification.

As a result of the step S39, if the downloadable data are middleware module, at step S40, it is determined
30 whether its version is the same as the version of the pre-established middleware module.

If the version of the middleware module to be downloaded is the same as the version of the pre-established middleware module, the download is suspended
35 and the logic flow goes to the step S30 to continue to

monitor the broadcast stream. If the versions are not the same, at step S50, it is determined whether the middleware module is capable of accessing to the mobile terminal.

If the middleware module is not capable of accessing
5 to the mobile terminal, at step S41, the middleware module is extracted from the broadcast stream and stored in the memory 23.

Subsequently, at step S42, it is checked whether there is any application executed on the middleware.

10 If there is no application executed, at step S44, the middleware module is set up. If there is an application executed, at step S43, the application in execution is suspended and then, at step S44, middleware module is set up.

15 Subsequently, at step S45, it is checked whether the application is suspended temporarily after the completion of the middleware setup. If the application is suspended temporarily, at step S46, the application is resumed and then the logic flow goes back to the step S30 to continue
20 to monitor the broadcast stream. If the application is not in the state of temporary suspension, the logic flow goes back to the step S30 to continue to monitor the broadcast stream.

Meanwhile, if the middleware is capable of accessing
25 to the mobile communication terminal, at step S52, it is checked whether there is a request for accessing to the mobile communication network from the user.

Then, if there is the request for accessing to the mobile communication network from the user, at step S54, it
30 is checked whether the downloaded software and data can execute the request of the user.

If it is determined that the request from the user cannot be executed at the step S54, the logic flow goes back to the step S30 to continue to monitor the broadcast
35 stream. If the request from the user can be executed, at

step S56, user authentication and a mobile terminal accessing program can be executed and, at step S58, the interactive data broadcasting application is executed.

For instance, if the downloaded software has control
5 signals and data that can support only the mobile terminals produced by an A company and the user requests a mobile communication service of a B company, it is determined that the service request cannot be executed and the logic flows jumps back to the starting point 30. If the service request
10 can be executed, at step S56, a user authentication process is performed and a mobile communication network connection process is performed for interactive data communication. If the access to the communication network is successful, at step S58, an application program for interactive data
15 broadcasting is carried out.

Meanwhile, as a result of the step S39, if the kind of the downloadable data is middleware plug-in data, at step S60, it is checked whether the Multipurpose Internet Mail Extensions (MIME) format of the downloadable middleware
20 plug-in data, which is described to inform the type of application data to be used for the plug-in data, is registered or not in comparison with an MIME format list in the receiving apparatus.

If the MIME format is registered in the pre-
25 established list at the step S60, the plug-in process is ended and the logic flow goes back to the step S30 to continue to monitor broadcast stream. If the format is not registered in the pre-established list, that is, if the MIME format is new, at step S62, data for middleware plug-
30 in are extracted from the broadcast stream and stored in the memory 23.

Subsequently, at step S64, plug-in software is set up and it is registered as a new MIME format and the logic flow goes back to the step S30.

35 The method of the present invention can be embodied as

a program and stored in a computer-readable recording medium, such as CD-ROM, RAM, ROM, floppy disks, hard disks, magneto-optical disks and the like. Since the process can be easily implemented by those of ordinary skill in the art, further description on it will not be provided herein.

While the present invention has been described with respect to certain preferred embodiments, it will be apparent to those skilled in the art that various changes and modifications may be made without departing from the scope of the invention as defined in the following claims.

What is claimed is:

1. A data broadcast receiving apparatus capable of supporting an interactive service, comprising:

5 a demultiplexing means for dividing signals transmitted from the outside into signals of a kind;

a controlling means for controlling elements of the data broadcast receiving apparatus, receiving and outputting contents divided in the demultiplexing means;

10 a download processing means for receiving downloadable data divided in the demultiplexing means, determining the kind of the downloadable data, and performing upgrade by downloading the downloadable data; and

a mobile terminal accessing means for accessing to a
15 mobile communication network based on the downloadable data.

2. The data broadcast receiving apparatus as recited in claim 1, wherein the controlling means includes:

20 a middleware processing means for processing middleware of the data broadcast receiving apparatus, controlling the download processing means, receiving a middleware module and a middleware plug-in software included in the downloadable data from the download
25 processing means; and

an operating means for operating the data broadcast receiving apparatus and controlling the middleware processing means and the mobile terminal accessing means.

30 3. The data broadcast receiving apparatus as recited in claim 1, wherein the download processing means determines the kind of the downloadable data by using a downloadable data information descriptor describing data broadcast specification information.

4. The data broadcast receiving apparatus as recited in claim 3, wherein the downloadable data information descriptor includes at least one among Program Specific Information (PSI) of the Moving Picture Experts
5 Group (MPEG)-2 system, Data Service Table (DST) of the Advanced Television Systems Committee (ATSC) data broadcasting, Application Information Table (AIT) of the DVB-Multimedia Home Platform (MHP), and System Information (SI) of the Digital Multimedia Broadcasting (DMB).

10

5. A method for upgrading software by using downloaded data inputted from the outside in a data broadcast receiving apparatus, comprising the steps of:

- a) selecting downloadable data from broadcast stream
15 in the data broadcast receiving apparatus;
- b) determining the kind of the downloadable data; and
- c) upgrading the software according to the kind of the downloadable data.

20 6. The method as recited in claim 5, wherein the step a) includes:

- a1) monitoring the presence of a downloadable data information descriptor in the broadcast stream; and
- a2) extracting data identification information from
25 the downloadable data information descriptor.

7. The method as recited in claim 6, wherein the downloadable data information descriptor includes at least one among Program Specific Information (PSI) of the Moving
30 Picture Experts Group (MPEG)-2 system, Data Service Table (DST) of the Advanced Television Systems Committee (ATSC) data broadcasting, Application Information Table (AIT) of the DVB-Multimedia Home Platform (MHP), and System Information (SI) of the Digital Multimedia Broadcasting
35 (DMB).

8. The method as recited in claim 7, wherein the kind of the downloadable data is determined based on the data identification information in the step b).

5

9. The method as recited in claim 5, wherein the kind of the downloadable data includes a middleware module for accessing to a mobile communication terminal and a middleware plug-in.

10

10. The method as recited in claim 9, wherein the step c) includes the steps of:

c1) upgrading the software by using the middleware module; and

15 c2) upgrading the software by using the middleware plug-in.

11. The method as recited in claim 10, wherein the step c) includes the steps of:

20 c3) determining whether the version of the downloaded middleware module is the same as the version of the pre-established middleware version; and

c4) setting up the downloaded middleware module, if the version of the downloaded middleware module is not the same as the version of the pre-established middleware version.

25

12. The method as recited in claim 11, wherein the step c) includes the steps of:

30 c5) suspending an application in execution temporarily; and

c6) executing the temporarily suspended application after the setup of the middleware module.

35 13. The method as recited in claim 10, wherein the

step c2) includes the steps of:

c2-1) checking whether the Multipurpose Internet Mail Extensions (MIME) format of the downloaded middleware plug-in is registered;

5 c2-2) if the format of the downloaded middleware plug-in is new, registering the format of the downloaded middleware plug-in; and

c2-3) setting up the downloaded middleware plug-in.

10 14. The method as recited in claim 5, further comprising the step of:

d) receiving and processing a request for accessing to a mobile communication network from the user.

15 15. The method as recited in claim 14, wherein the step d) includes the steps of:

d1) checking whether the downloadable data include a module capable of accessing to a mobile terminal;

20 d2) if the access to the mobile terminal is possible, checking whether the request for accessing to the mobile communication network from the user can be executed; and

25 d3) if the request for accessing to the mobile communication network from the user can be executed, accessing to the mobile communication network by executing user authentication and a mobile terminal accessing program.

30 16. The method as recited in claim 15, wherein whether the request for accessing to the mobile communication network from the user can be executed is determined based on module information of the mobile terminal of the user or communication company information.

35 17. A data broadcast receiving apparatus supporting an interactive service, comprising:

a demultiplexing means for dividing signals from the outside into signals of a kind;

a controlling means for controlling elements of the data broadcast receiving apparatus, receiving and
5 outputting contents divided in the demultiplexing means;

a download processing means for receiving downloadable data divided in the demultiplexing means, determining the kind of the downloadable data, and performing upgrade by downloading the downloadable data; and

10 a mobile terminal accessing means for accessing to a mobile communication network based on the downloadable data.

1/3

FIG. 1





FIG. 2



2/3

FIG. 3





FIG. 4



INTERNATIONAL SEARCH REPORT

International application No.
PCT/KR2004/002817

A. CLASSIFICATION OF SUBJECT MATTER**IPC7 H04N 7/173**

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

Int.Cl.7 G06F 9/44, H04B 7/155, 7/26, H04N 7/173

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean Patents and applications for inventions since 1975

Korean Utility models and applications Utility models for since 1975

Japanese Utility models and applications for Utility models since 1975

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKIPASS

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO03009136A1 (REN YUQING) 30.01.2003 - See the whole document	1, 5, 17
Y	KR1020010009860 (LG INFORMATION & COMMUNICATIONS LTD.) 05.02.2001 - See the whole document	1, 5, 17
A	EP0814415A2 (MATSUSHITA ELECTRIC IND CO LTD) 29.12.1997 - See the whole document	1-17
A	WO03083647A1 (NTT DOCOMO, INC.) 09.10.2003 - See the whole document	1-17

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

28 JANUARY 2005 (28.01.2005)

Date of mailing of the international search report

28 JANUARY 2005 (28.01.2005)

Name and mailing address of the ISA/KR



Korean Intellectual Property Office
920 Dunsan-dong, Seo-gu, Daejeon 302-701,
Republic of Korea

Facsimile No. 82-42-472-7140

Authorized officer

KWON, KI WON

Telephone No. 82-42-481-8123



NOT AVAILABLE COPY

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/KR2004/002817

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
W003009136A1	30.01.2003	EP1410181A1	21.04.2004
KR1020010009860	05.02.2001	none	
EP0814415A2	29.12.1997	AU2496597A	15.01.1998
		AU708716B2	12.08.1999
		CN1170904A	21.01.1998
		JP10003451A	06.01.1998
		KR268027B1	16.10.2000
		US5970511A	19.10.1999
W003083647A1	09.10.2003	EP1496430A1	12.01.2005

BEST AVAILABLE COPY